





# PSU24-5A Intelligent Network Power Supply Unit

### **Description**

To support heavy consumption application, part of the fire alarm devices require for external 24VDC power supply. PSU24-5A Intelligent Network Power Supply Unit is the suitable choices. The supply source is 230 VAC, 50/60 Hz. Nominal output load is 5A/24VDC. The built-in charger and maintenance-free sealed lead acid batteries ensure the standby supply.


With additional addressable feature, PSU24-5A is also possible to be connected into fire alarm loop. With the address control, it is able to report fault of mains loose, battery loose or output broken to the fire panel.


### **Features and Benefits**

- Seamless convert between mains and standby power sources.
- Built-in battery recharge with temperature compensation.
- Battery over-discharge protection.
- Indication of output voltage, output current, mains fault, battery fault, output fault and charger fault.
- Local audio fault indication.

### **Installation Data**

PSU24-5A power supply unit is wall-mount/flush-mount combined. Its appearance and the mounting holes are shown here.





### **Terminals**

The terminals of the PSU are shown below.



Power Fault Battery Fault Mains Fault



L, N, PG: AC input +,-: Battery input 24V, GND: 24VDC output

Z1, Z2 (on the display board): Loop connection
Power Fault: 24VDC fault contact, 30VDC/2A
Battery Fault: Battery fault contact, 30VDC/2A
Mains Fault: Mains fault contact, 30VDC/2A

2.0mm<sup>2</sup> or above fire cable is recommended for 24VDC line, 1.0mm<sup>2</sup> or above fire cable is recommended for other signal lines, but subject to local codes.

# **Certificates and Compliance**

Standards: CE / EN54-2 / EN54-4

BS5839-1 Compliant

WEEE & RoHS Compliant

# **Technical Specification**

Mains Power	230VAC+10%/-15%, 50/60Hz
Battery Size	24VDC /12Ah
Rated Output	5A/26.5V DC
Programming	Electronically addressing, from address 1 to 242
Ingress Protection	IP20
Operating Environment	Temperature: 0°C ~ +40°C Relative humidity ≤95%, non condensing
Dimension	400mm × 318mm × 128mm

# **Order Information**

Part No.	PSU24-5A
Device Name	Intelligent Power Supply Unit
Order Code	1353145

# **Compatible Panels**

GST-IFP8 Intelligent Fire Alarm Control Panel GST200-2 Series Intelligent Fire Alarm Panels GST200N Series Intelligent Fire Alarm Panels

## **Accessories and Tools**



Part No.: P-9910B

Device name: Handheld Programmer

Order Code: 1274894