

AXIS Camera Station S1016 Mk II Recorder

Out-of-the box ready workstation for high-definition surveillance

AXIS Camera Station S1016 Recorder is an out-of-the-box ready workstation validated for reliable high-definition surveillance up to 4K. It is preloaded with AXIS Camera Station video management software with universal licenses for 16 channels and other necessary system software. It is preconfigured to minimize installation time. AXIS S1016 has validated hardware components and extendable storage capacity, and includes three-year hardware warranty with on-site replacement service. AXIS Camera Station offers an intuitive user interface and allows users to take full advantage of Axis' wide range of video surveillance cameras and other IP products. It also supports integration of third party IP cameras.

- > Ease of installation
- > Validated with extensive support
- > High-definition surveillance up to 4K
- > AXIS Camera Station included
- > Full compatibility with Axis' products







| | AXIS Camera Station |
|----------------------|---|
| Licenses | 16 AXIS Camera Station universal licenses included, can be upgraded up to 32 licenses (sold separately) |
| Processor | Intel® i5 4570S, Quad Core, 2.90 GHz Turbo, 6MB |
| Memory | 8GB (2x4GB) 1600 MHz DDR3 |
| Storage | 8 TB (2x4TB) Enterprise Class HDD, 7200 rpm, SATA 6Gb/s , no RAID. Possible to add 2 additional HDD $^{\rm a}$ |
| Graphic card | AMD Radeon R5 A240 1 GB DDR3 2 monitors supported |
| Operating system | Microsoft Windows 10 IoT Enterprise |
| Video streaming | Live view: Up to 25 camera split views or 1 x 4K camera view Playback: 4 x 1080p camera split views or 1 x 4K camera view |
| Recording | Qualified for recording up to 32 video channels with a total recording rate up to 256 Mbit per second. |
| General | |
| Power | Max 365 W, 100 V AC to 240 V AC |
| Connectors | 6xUSB 2.0, 4xUSB 3.0, 1xDisplay Port, 1xDual link DVI-I Ethernet LAN 10/100/1000 Mbit, Line-in/out connectors, Computer mouse and keyboard connectors |
| Operating conditions | 5 °C to 45 °C (41 °F to 113°F) |

| S1016 Mk II Recorder | |
|----------------------|--|
| Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) |
| Approvals | EN/IEC/UL 60950-1, FCC part 15, class B, VCCI V-3, VCCI V-4, AS/NZS CISPR 22, class B, ICES-003/NMB-003, KCC KN22 Class B, KN-24,EN 62311, EN 55022, EN 55024, EN/IEC 61000-3-2, EN/IEC 61000-3-3, EN 300 328, EN 301 893, EN 301 489-1, EN 301 489-17 |
| Dimensions | 360 x 175 x 417 mm (14.17 x 6.89 x 16.42 in) |
| Weight | 9.5 kg (20.9 lb) |
| Included accessories | Installation guide, Keyboard (International/US), Computer mouse, Power cable |
| Optional accessories | AXIS T8310 Video Surveillance Control Board AXIS P8221 I/O Audio Module AXIS A1001 Network Door Controller AXIS Camera Station S9001 MkII Desktop Terminal AXIS Camera Station S9002 Desktop Terminal |
| Warranty | Axis 3-year warranty, see www.axis.com/warranty |

a. For more info www.axis.com/support

AXIS Camera Station

For details about AXIS Camera Station features and functions please see Data Sheet on www.axis.com

Environmental responsibility: www.axis.com/environmental-responsibility

