

# DMN700G

## Manual Callpoint, Emergency Door Release, Flush Mount, Green, Free Contact, Break Glass

### General

---

Installation efficiency, flexibility and full compliance with the latest standards are at the heart of the new MCP indoor call point range.

### Installation

---

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

### Options and approvals

---

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.

Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard



### Details

---

- Specifically for door security and evacuation
- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

# DMN700G

Manual Callpoint, Emergency Door Release, Flush Mount, Green, Free Contact, Break Glass

## Technical specifications

---

### Physical

---

Net weight	110 g
------------	-------

---

### Environmental

---

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP24D

---

### Cable Termination

---

0.5 - 2.5 mm <sup>2</sup>
---------------------------

---

### Max. contact rating (resistive load)

---

2A @ 30 VDC
-------------

---

### Mechanical

---

Material	PC/ABS
----------	--------

---

