

## **Universal gateway for PC (software)**



## Part-No. 013590

Gateway software as a standalone solution for the allocation of data points on host control center systems via OPC, ESPA 4.4.4.



Phone: +49 2131 40615 600

Faximile: +49 2131 40615 606

Hardware and software requirements:

Pentium 3 GHz or higher, min. 512 MB RAM, min. 1 GB hard disk, XGA graphics card with min. 4 MB video memory, monitor with 1024 x 768 pixels or more, sound card with external speakers, Windows XP Professional SP2 and Windows 2003 Server, Windows Vista, Internet Explorer 6.0 or higher.

Part No. 013590 may only be ordered in connection with Part No. 013618.

Please use order form on www.esser-systems.com.

## Features:

- Compatible with Windows XP Professional SP2, Windows of 2003 servers and Windows Vista
- · Modular construction and freely programmable
- Direct control of the network devices
- · List of measures to be taken for fire-fighting forces
- Individual allocation of usage rights incl. priority scheduling
- Integrated simulation-functions
- · Extensive recording of events and operations
- · Visualization of messages
- Up to 12 active graphics simultaneously representable
- · Integration of video sequences possible
- Information output via Windows print manager to multiple printers etc.
- · Time program/calendar function
- · Integrated database standard
- Activation of other programs from WINMAGplus possible
- Efficient programming language (SIAS) for customer-specific adjustment of interface and processes in case of alarm
- · Remote control possible via modem (optional)
- 10 printers per workstation possible
- Multiple monitors can be used. 4 of 8 screens may be selected.

Subject to change without notice! © Honeywell International Inc.