

PRS-CRF Call Stacker

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Records calls for automatic playback to previously occupied zones (call stacker)
- ▶ Acoustic feedback suppression by recording a call with delayed broadcast (time shifter)
- ▶ Possibility to monitor a call before broadcasting
- ▶ Records and/or plays back up to eight calls simultaneously
- ▶ Stores up to 16 calls

The Call Stacker is a small unit that records calls that cannot be sent to all required zones because some are occupied by a higher priority call. The unit can store up to 16 calls in high-quality format with a maximum of three minutes for each call, including chimes and pre-recorded messages. Playback of a call can start while it is still being recorded. The unit can record and/or playback up to eight calls simultaneously. More units can be added to a system in order to increase the number of recordable calls. Units can be connected to the Praesideo network at any place.

Functions

The functions of the call stacker are configured as part of a call macro in Praesideo. Here it is configured whether a call will be recorded for playback later in case zones are occupied or the call is being overruled in some zones.

When these zones become available again, the call is automatically repeated to these remaining zones, to all at once or cascaded to each zone individually.

After a call is finished completely, it will be deleted from memory.

The unit has a configurable time-out period to delete outdated unsent calls.

The call stacker can also be used as time shifter to avoid acoustic feedback from a loudspeaker to the active microphone. The call is recorded and broadcast after the recording has finished. The call can be pre-monitored before broadcast with the option to cancel the call.

Time shifting and call stacking can be combined. Logging of the call and all its playbacks is supported, but the recorded calls do not survive a power down and are not supervised, so the call stacker function should not be relied upon for emergency calls. The unit is configurable via the Praesideo network controller (web browser interface).

Controls and indicators

- Two LED indicators for power and network status

Interconnections

- Two Praesideo network connectors
- RJ11 service connector (JTAG)

Certifications and approvals

Safety	acc. to IEC 60065 / EN 60065
Immunity	acc. to EN 55103-2 / EN 50130-4 / EN 50121-4
Emissions	acc. to EN 55103-1 / FCC-47 part 15B

Emergency	acc. to EN 60849 / EN 54-16 / ISO 7240-16
Maritime	acc. to IEC 60945

Region	Certification	
Europe	CPR	EU_CPR
	CE	
	CE	COC
	CE	CertAlarm
	CE	DOP
	GL	

Parts included

Quantity	Component
1	PRS-CRF Call Stacker
1	Mounting bracket

Technical specifications

Electrical

Power consumption	4.2 W
-------------------	-------

Performance

Frequency response	20 Hz to 20 kHz (-3 dB)
S/N	> 85 dB
Crosstalk	<-85 dB

Mechanical

Dimensions (H x W x H)	
Without bracket	27 x 243 x 80 mm (1.1 x 9.6 x 3.1 in)
With bracket	34 x 243 x 84 mm (1.3 x 9.6 x 3.3 in)
Weight	0.7 kg (1.5 lb)
Mounting	Bracket (two screws)
Color	Charcoal

Environmental

Operating temperature	-5 °C to +55 °C (+23 °F to +131 °F)
Storage temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Relative humidity	15 % to 90 %
Air pressure	600 to 1100 hPa

Ordering information

PRS-CRF Call Stacker

Compact unit with mounting clamp, provides a recording and playback function for up to 8 simultaneous calls for previously occupied zones or for pre-broadcast monitoring, can store up to 16 calls, powered from Praesideo network.

Order number **PRS-CRF**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com