



## Основные характеристики

- 4/8/16-канальные цифровые видеорегистраторы DVR
- 25 к/с на канал в разрешении 960H
- Максимальное разрешение 960 x 576
- Удаленный доступ по web / со смартфона
- HDMI выход
- Установка до 5 HDD

## Универсальность

егистраторы DigiMaster серии позволяют вести запись с высоким разрешением 960 x 576, что позволяет получить максимум информации от аналогового видеонаблюдения при том сохранится скорость записи 25 к/с на канал.

Экспорт видео осуществляется на DVD-носитель или FTP-сервер.

В комплекте идет программное обеспечение DM-View, позволяющее вести мониторинг до 64 каналов на одном рабочем месте оператора. Просмотр с мобильных устройств через приложение DM-View.

Order number	Product description
DR-8FX5 - 8-Kanal / 5 HDD DR-16FX5 - 16-Kanal / 5 HDD DR-4FX1 - 4-Kanal / 1 HDD DR-8FX2 - 8-Kanal / 2HDD DR-16FX2 - 16-Kanal / 2 HDD	Pentaplex Digitalrecorder, 960H, H.264 compression, LINUX OS, LAN, HDMI-out, 25 images per second and channel @ 960H

# Digimaster 960H



## Accessoires

Order number	Product description
ZRS-HDD1000	1TB S-ATA HDD
ZRS-HDD2000	2TB S-ATA HDD
ZRS-HDD3000	3TB S-ATA HDD
NR-RM1	Rackmount adapter for DR-8FX2 / DR-16FX2
NR-RM2	Rackmount adapter for DR-8FX5 / DR-16FX5

## Advantages for the installer

Optionally, a rack-mount system is available. Furthermore, the menu interface that can be operated with the mouse is designed in a clearly structured and logical manner. This way, the system can be configured quickly.



Technical specifications	DR-8FX5	DR-16FX5
Video standard	PAL / NTSC	
Compression format	H.264	
Video input	8 x BNC 1 Vp-p/75Ω	16 x BNC 1 Vp-p/75Ω
Spot output	Aux 1 : (1Vpp, 750ohm) [ 1ch / 4ch / 9ch programmable ] 2 : (1Vpp, 750ohm) [ 1ch / 4ch ]	Aux 1 : (1Vpp, 750ohm) [ 1ch / 4ch / 9ch / 16ch programmable ] 4 : (1Vpp, 750ohm) [ 1ch / 4ch ]
Loop output	8 x BNC 1 Vp-p/75Ω	16 x BNC 1 Vp-p/75Ω
Monitor output	HDMI / VGA	
Audio input	8CH (10KOhm, 2.8Vpp)	16CH (10KOhm, 2.8Vpp)
Audio output	1CH (600Ohm, 2.8Vpp)	
Alarm input	10CH(8CH+2CH), Pulled up to 5V via 10KOhm	18CH(16CH+2CH), Pulled up to 5V via 10KOhm
Alarm output	4CH, RELAY (125VAC, 60VDC)	8CH, RELAY (125VAC, 60VDC)
Hard disk quantity	max. 5	
Operating system	Linux / Pentaplex	
Recording format	CIF (352 x 240/288), 2CIF (704 x 240/288), 4CIF (704 x 480/576), 960H (960 x 480/576)	
Recording mode	Continuous / Movement / Alarm / Panic	
Recording rate	Up to 200fps @ 960H	Up to 400fps @ 960H
Replay	Up to 8 Channels simultaneous	Up to 16 Channels simultaneous
Events	Continuous / Movement / Video loss / External alarm	
Movement sensor	Yes (20x12 fields, 30 sensitivity levels, day/night independently configurable)	
Interfaces	2 x RS-485, RS-232 2 x 10/100/1000 BaseT, 3 x USB, E-SATA	
Time/date settings	GMT timezone, Auto DST, NTP	
Remote access	Yes (IE, DMS Lite, App)	
Export	AVI, FTP	
OSD languages	English, German, French, Spanish, Dutch, Polish, Czech	
Protocoles	Pelco D/P, MesaDome, D-Max, Fastrax II, Ganz PT v3.2, SCC641/643a, Spd3300, Multix, MRX1000, WV-cs850-csr604, PTC-400c/-200, Takex, LPT-A100L, interM, Vitek, Lilin, Max-pro, VCL	
Access authorisation	Configurable	
Fan	2	
Operating environment	0°C ~ 40°	
Operating voltage	SMPS, 100W, 100~220V AC, 50-60Hz	
Dimensions (W x H x D)	2U ( 430mm x 88.4mm x 367mm )	
Weight	9.0 kg	
Accessories (incl.)	Mouse, Remote control	

CBC (Europe) GmbH  
Hansaallee 191  
D-40549 Düsseldorf  
T: +49-(0)211 53 06 70  
F: +49-(0)211 53 06 71 80  
info@cbc-europe.com  
www.cbc-europe.com

CBC (Poland) Sp.z.o.o.  
Oddział w Warszawie  
ul. Anny German 15  
01-794 Warszawa  
T: +48-(0)22 6 33 90 90  
F: +48-(0)22 6 33 90 60  
info@cbcpoland.pl  
www.cbcpoland.pl

CBC Russia Moscow Rep. office  
Office 503B World Trade Center  
12 Krasnopresnenskaya nab.  
RU-11123610 Moscow  
T: +7-495 258 2161  
F: +7-495 258 2160  
info@cbc.ru  
www.cbc.ru

CBC (Europe) Ltd. Ufficio di Milano  
Via E. Majorana, 2  
I-20054 Nova Milanese  
T: +39-0362 36 50 79  
F: +39-0362 4 00 12  
info@cbc-europe.it  
www.cbc-europe.it

CBC CORPORATION (INDIA), PRIVATE LTD  
2F B Wing, Marwah Centre  
Krishanlal Marwah Marg  
Andheri East, Mumbai 400 072, India  
T: +91 22 2857 9798  
F: +91 22 6649 1708  
enquiry@cbcindia.jp

CBC (EUROPE) GmbH UK Branch  
Unit 9 Garrick Road Industrial Estate  
Irving Way  
London  
NW9 9AQ  
F: +44-(0)20 82 02 33 87  
info@cbcuk.com  
www.cbc-europe.com

# Digimaster 960H



## Accessoires

Order number	Product description
ZRS-HDD1000	1TB S-ATA HDD
ZRS-HDD2000	2TB S-ATA HDD
ZRS-HDD3000	3TB S-ATA HDD
NR-RM1	Rackmount adapter for DR-8FX2 / DR-16FX2
NR-RM2	Rackmount adapter for DR-8FX5 / DR-16FX5



Technical specifications	DR-4FX1	DR-8FX2	DR-16FX2
Video standard	PAL / NTSC		
Compression format	H.264		
Video input	4 x BNC 1 Vp-p/75Ω	8 x BNC 1 Vp-p/75Ω	16 x BNC 1 Vp-p/75Ω
Spot output	1 (1Vpp, 750ohm) [ 1ch / 4ch programmable ]		
Loop output	-	-	-
Monitor output	HDMI / VGA		
Audio input	4CH (10KOhm, 2.8Vpp)	4CH (10KOhm, 1Vrms)	
Audio output	1CH (600Ohm, 2.8Vpp)	1CH (600Ohm, 1Vrms)	
Alarm input	4CH, Pulled up to 5V via 10KOhm		
Alarm output	1CH, RELAY (125VAC, 60VDC)		
Hard disk quantity	1	2	
Operating system	Linux / Pentaplex		
Recording format	CIF (352 x 240/288), 2CIF (704 x 240/288), 4CIF (704 x 480/576), 960H (960 x 480/576)		
Recording mode	Continuous / Movement/ Video loss / External alarm		
Recording rate	Up to 100fps @ 960H	Up to 200fps @ 960H	Up to 400fps @ 960H
Replay	Up to 4 Channels simultaneous	Up to 8 Channels simultaneous	Up to 16 Channels simultaneous
Events	Continuous / Movement/ Video loss / External alarm		
Movement sensor	Yes (20x12 fields, 30 sensitivity levels, day/night independently configurable)		
Interfaces	1 x RS-485, 1 x 10/100/1000 BaseT, 2 x USB		
Time/date settings	GMT timezone, Auto DST, NTP		
Remote access	Yes (IE, DMS Lite, App)		
Export	AVI, FTP		
OSD languages	English, German, French, Spanish, Dutch, Polish, Czech		
Protocoles	Pelco D/P, MesaDome, D-Max, Fastrax II, Ganz PT v3.2, SCC641/643a, Spd3300, Multix, MRX1000, WV-cs850/-csr604, PTC-400c/-200, Takex, LPT-A100L, interM, Vitek, Lilin, Maxpro, VCL		
Access authorisation	Configurable		
Fan	-	1	
Operating environment	0°C ~ 40°		
Operating voltage	12V DC, Adaptor, 3.3A, 100 ~ 240V AC, 50-60Hz		
Dimensions (W x H x D)	1U ( 255.6mm x 44.2mm x 173mm )	1U ( 305mm x 44.1mm x 298.2mm )	
Weight	2kg	3.5kg	
Accessories (incl.)	Mouse, Remote control		

CBC (Europe) GmbH  
Hansaallee 191  
D-40549 Düsseldorf  
T: +49-(0)211 53 06 70  
F: +49-(0)211 53 06 71 80  
info@cbc-europe.com  
www.cbc-europe.com

CBC (Poland) Sp.z.o.o.  
Oddział w Warszawie  
ul. Anny German 15  
01-794 Warszawa  
T: +48-(0)22 6 33 90 90  
F: +48-(0)22 6 33 90 60  
info@cbcpoland.pl  
www.cbcpoland.pl

CBC Russia Moscow Rep. office  
Office 503B World Trade Center  
12 Krasnopresnenskaya nab.  
RU-11123610 Moscow  
T: +7-495 258 2161  
F: +7-495 258 2160  
info@cbc.ru  
www.cbc.ru

CBC (Europe) Ltd. Ufficio di Milano  
Via E. Majorana, 2  
I-20054 Nova Milanese  
T: +39-0362 36 50 79  
F: +39-0362 4 00 12  
info@cbceurope.it  
www.cbceurope.it

CBC CORPORATION (INDIA), PRIVATE LTD  
2F B Wing, Marwah Centre  
Krishnalal Marwah Marg  
Andheri East, Mumbai 400 072, India  
T: +91 22 2857 9798  
F: +91 22 6649 1708  
enquiry@cbcindia.jp

CBC (EUROPE) GmbH UK Branch  
Unit 9 Garrick Road Industrial Estate  
Irving Way  
London  
NW9 9AQ  
F: +44-(0)20 82 02 33 87  
info@cbcuk.com  
www.cbceurope.com