


ISC-RSC2-S Shutter door contact

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Conventional shutter door contact
- ▶ VdS class B/EN 50131-2-6 Grade 2
- ▶ High level of mechanical strength
- ▶ Conventional perimeter protection

Conventional shutter door contacts are used to monitor shutter, sliding and garage doors.

Certifications and approvals

Region	Regulatory compliance/quality marks	
Germany	VdS	
Europe	CE	[ISC-MCLS3-S, ISC-MCOLS3-S, ISC-RSC2-S, ISC-RSC3-S]
	EN5013 1	
Russia	GOST	EAC

Installation/configuration notes

Installation information

- For doors < 1.5 m, one shutter door contact is required. For doors > 1.5 m, use two shutter door contacts. Take note of the permissible installation tolerances.
- The shutter door contact consists of a sealed magnetic switch and a magnet in a plastic housing. The connection cable is protected over a length of 1 m by flexible metal conduit.

- The magnetic switch is installed at ground level (requires a flat surface). The switch will not be damaged if driven over by vehicles with rubber tires. However, the magnetic switch must not be used as a door stopper.
- The supply lines must be electrically measured prior to connection.

Parts included

Quantity	Component
1	Shutter door contact
1	Magnet
1	Cable
1	Installation material

Technical specifications

Electrical

Maximum load in W	3
Maximum switching voltage in VDC	30
Minimum switching current in mA	0.01
Maximum switching current in mA	100

Mechanical

Minimum installation distance in cm	2
Maximum installation distance in cm	4
Reed contacts	Normally open
Material (magnet)	AlNiCo 500
Material (cable)	Plastic
Color	Gray
Dimension in cm (H x W x D) (switch)	1.5 x 4 x 1.35
Dimension in cm (H x W x D) (magnet)	6.5 x 4.2 x 3.5
Weight in g (including cable and magnet)	250
Cable type	LiYY-ZGL 4 x 0.14 mm ² SN, white, suitable for LSA-PLUS insulation displacement technology

Cable length in m	4
Cable protection tube	Flexible metal, diameter: 6/9 mm, covered in plastic, gray
Cable protection tube length in m	1
Switch cycles	10 ⁷

Environmental

Minimum operating temperature in °C	-40
Maximum operating temperature in °C	70
Protection class	67
Environmental class (VdS)	III
Environmental class (EN)	IIla

Ordering information**ISC-RSC2-S Shutter door contact**

For monitoring shutter, sliding, and garage doors
Order number **ISC-RSC2-S**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia