

IQ8Alarm Plus/So sounder, white



Part-No. 807205W

Approval: VdS

Addressable, completely bus supplied and short circuit / open circuit resilient fire alarm sounder in compliance with EN 54?3 with integrated signaling tones for acoustic alarm signaling.

With up to 20 different programmable signaling tones including DIN tone in accordance with DIN 33404 Part 3.

The volume can be set to 8 different levels. The load factor can be set to 2 different levels

Signaling device with flat base, suitable for wall and ceiling mounting. Optionally, IP base Part No. 806201 with side cable entry and weatherproof protection can be installed.

Features:

- · Completely bus supplied alarm device
- · Powered loop compatible
- · Low power consumption
- · Up to 64 alarm devices for each powered loop
- · Each alarm device has built-in isolator
- · Synchronous trigger

Acoustic alarm properties:

- EN 54-3 compliant
- · High acoustic pressure
- · Volume programmable in 8 steps via tools 8000
- 20 different signaling tones, including DIN tone

Acoustic

Load factor acoustic 1,5 *1 /

Sound level 91 *1 / 97 dB (A) +/- 2 dB @ 1 m / @ 90° angle / @ DIN Tone

Specification EN 54-3: 2001 / A1: 2002 / A2 : 2006 / -17: 2005

EN 54-3 Sounder

Common technical data:

Operating voltage 14 ... 42 V DC (via powered loop)

Quiescent current @ 19 V DC 55 μ A approx. 300 μ A @ 42 V Ambient temperature -10 °C ... 55 °C Storage temperature -25 °C ... 75 °C

Air humidity < 95 % (non-condensing)

Type of protection IP 43 *2

IP 56 with IP base 806201 *3
Housing Polycarbonate plastic
Color white, similar to RAL 9010
Weight approx. 300 g (with base)
Dimensions Ø: 112 mm D: 78 mm

Ø: 112 mm D: 93 mm (with IP base)

Declaration of Performance DoP-21430171215



When using the flat IP base the db output reduces by an average of 3 dB.

1 *1 Factory setting, configuration with service- and programming software tools 8000

*2 IP 21C acc. EN 54-3 / -23

*3 Do not use the base for acoustic alarm applications in compliance with EN 54-3 Replacement for Part No. 807205

Accessories:

806201 IP base, white

Phone: +49 2131 40615 600

Faximile: +49 2131 40615 606