



FLM-420-EOL2W-W EOL Module LSN



The EOL module terminates LSN stubs or T-taps according to EN 54-13.

It detects LSN line faults according to EN 54-13 and reports them to the fire panel via LSN. The reports are displayed on the panel controller.

Certifications and Approvals

Region	Certification	
Germany	VdS	G 210008 FLM-420-EOL2W-W
Europe	CE	FLM-420-EOL2W-W
	CPD	0786-CPD-20927 FLM-420-EOL2W-W

Installation/Configuration Notes

According to DIN VDE 0833-2 there are the following restrictions:

- Max. 32 automatic fire detectors in a LSN stub or T-tap.
- Max. 10 manual call points in a LSN stub or T-tap.

Parts Included

Qty.	Components
1	FLM-420-EOL2W-W EOL Module LSN

Technical Specifications

Electrical

Operating voltage	15 V DC to 33 V DC
Current consumption	< 1.5 mA

Mechanics

Housing material	ABS + PC Blend
Housing color	Signal white (RAL 9003)
Dimensions (Øx D)	76 x 30 mm
Weight	50 g

Environmental conditions

Permissible operating temperature	-20°C to 55°C
Permissible storage temperature	-25°C to 85°C
Permissible relative humidity	<96%, non condensing
Protection class as per IEC 60529	IP 40

Ordering Information

FLM-420-EOL2W-W EOL Module LSN **FLM-420-EOL2W-W**
for EN 54-13 compliant termination of LSN
stubs or T-taps

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.asia

Represented by