

# LH1-10M10E Horn Loudspeaker

www.boschsecurity.com



**BOSCH**

Invented for life



- ▶ High efficiency driver
- ▶ Excellent speech reproduction
- ▶ Provision for inside mounting of the optional line / loudspeaker supervision board
- ▶ Water-and dust protected to IP 65
- ▶ EN 54-24 certified

The LH1-10M10E high-efficiency horn loudspeaker, provides excellent speech reproduction and sound distribution for a wide scope of indoor and outdoor applications. It is ideal for sports grounds, parks, exhibitions, factories and swimming pools.

The LH1-10M10E is a rectangular shaped 10 W horn loudspeaker, made from aluminum. The edge of the horn is covered with a PVC profile for protection against impact damage. The rear cover of the horn is made from self-extinguishing ABS (acc. to class UL 94 V0).

The housing color is light grey (RAL 7035), and is water and dust protected.

## Functions

### Voice Alarm

Voice alarm loudspeakers are specifically designed for use in buildings, where the performance of PA systems is subject to official regulations. The LH1-10M10E is designed for voice alarm systems and is EN 54-24 certified and compliant with BS 5839-8 and EN 60849.

### Protection

The horn loudspeaker has built-in protection to ensure that in the event of a fire damage does not cause failure of the connected circuit. In this way, system

integrity is maintained, ensuring loudspeakers in other areas can still be used to inform people of the situation.

### Connections and Safety

The horn loudspeaker has a ceramic terminal block, thermal fuse, and heat-resistant, high-temperature wiring. Four primary taps are provided on the built-in matching transformer to allow selection of the output power.

The horn loudspeaker has a provision for internally mounting the optional line/loudspeaker supervision board.

## Certifications and approvals

All Bosch loudspeakers are designed to withstand operating at their rated power for 100 hours in accordance with IEC 268-5 Power Handling Capacity (PHC) standards. Bosch has also developed the Simulated Acoustical Feedback Exposure (SAFE) test to demonstrate that the speakers can withstand two times their rated power for short durations. This ensures extra reliability under extreme conditions, leading to greater customer satisfaction, longer operating life, and much less chance of failure or performance deterioration.

Safety	acc. to EN 60065
Emergency	acc. to EN 54-24 / BS 5839-8 / EN 60849
Water and dust protection	acc. to IEC 60529, IP 65
Wind-force	acc. to Bft 11

Region	Certification	
Europe	CE	
	CE	DOP

### Installation/configuration notes


The connection cable could be fed through a cable gland (PG 13.5) in the rear cover. For loop-through connection, the rear cover is fitted with a second hole (covered as standard supplied).

### Mounting


The horn loudspeaker is supplied, complete with sturdy adjustable steel U-shape bracket for mounting onto walls or ceilings, allowing the sound beam to be accurately directed.

### Simple Power Setting


The horn has a three-way ceramic terminal block with screw connection (including earth). Four primary taps are provided on the matching transformer to allow selection of nominal full-power, half-power or quarter-power and eighth-power radiation (in 3 dB steps).




Dimensions in mm (in)




Mounting bracket. Dimensions in mm (in)




Circuit diagram





Frequency response





Polar diagrams (Horizontal and Vertical, measured with pink noise)



Polar diagrams (Horizontal and Vertical, measured with pink noise)

Octave band sensitivity \*

	Octave SPL 1W/1m	Total octave SPL 1W/1m	Total octave SPL Pmax/1m
125 Hz	55.1	-	-
250 Hz	93.1	-	-
500 Hz	93.9	-	-
1000 Hz	102.0	-	-
2000 Hz	100.1	-	-
4000 Hz	97.2	-	-
8000 Hz	87.4	-	-
A-weighted	-	95.8	105.7
Lin-weighted	-	95.6	104.6

Octave band opening angles

	Horizontal	Vertical	
125 Hz	-	-	
250 Hz	360	360	
500 Hz	360	360	
1000 Hz	120	125	
2000 Hz	72	76	

4000 Hz	35	36	
8000 Hz	22	24	

Acoustical performance specified per octave

\* (all measurements are done with a pink noise signal; the values are in dB SPL)

### Parts included

Quantity	Component
1	LH1-10M10E Horn loudspeaker
1	PG 13.5 cable gland (fitted)

### Technical specifications

#### Electrical\*

Maximum power	15 W
Rated power (PHC)	10 W
Power tapping	10 / 5 / 2.5 / 1.25 W
Sound pressure level at 10 W / 1 W (1 kHz, 1 m)	112 / 102 dB (SPL)
Sound pressure level at 10 W / 1 W (1 kHz, 4 m)	87 / 76 dB (SPL)
Effective frequency range (-10 dB)	280 Hz to 5800 Hz
Opening angle at 1 kHz / 4 kHz (-6 dB)	
Horizontal	120° / 35°
Vertical	125° / 35°
Rated input voltage	100 V
Rated impedance	
	10 W 1000 Ohm
	5 W 2000 Ohm
	2.5 W 4000 Ohm
	1.25 W 8000 Ohm
Connector	Screw terminal block

\* Technical performance data acc. to IEC 60268-5

#### Mechanical


Dimensions (W x D)	(213 x 186) x 310 mm (8.39 x 7.32) x 12.2 in)
Weight	3.6 kg (7.93 lb)
Color	Light grey (RAL 7035)
Material (horn / rear cover)	Aluminum / ABS
Cable diameter	6 mm to 12 mm (0.24 in to 0.47 in)

### Environmental


Operating temperature	-25 °C to +55 °C (-13 °F to +131 °F)
Storage and transport temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative humidity	<95%

#### Note:

- The specification data is measured in an anechoic chamber, free field
- The reference axis is perpendicular to the center point of the front grille
- The reference plane is perpendicular to the center of the reference axis
- The horizontal plane is perpendicular to the center of the reference plane

 1438
Bosch Security Systems BV Torenallee 49, 5617 BA Eindhoven, the Netherlands 12 1438/CPD/0260
EN 54-24:2008  Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings  Horn Loudspeaker 10 W LH1-10M10E Type B DoP: LP062923

#### CE-label



Specified active equalization, required for EN54-24

### Ordering information

#### LH1-10M10E Horn Loudspeaker

Horn loudspeaker 10 W, rectangular, 8 x 7", aluminum/ABS material, U-bracket mounting, water and dust protected IP 65, EN54-24 certified, light gray RAL 7035.

Order number **LH1-10M10E**

**Represented by:**

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia