

Detector base with relay contact for IQ8Quad



Part-No. 805591

IQ8Quad detector base with relay contact output. Contact: floating NO or NC contact selectable via jumper. Settings on site: NO contact.

Features:

- Provides a voltage-free contact controlled by the remote output of a detector
- Draws negligible current
- A lot of space for wire connection
- Automatic closing of the loop bus wiring system for detector extraction
- Detector extraction locking is enclosed in the base

Current consumption	5 μ A (w/o detector, active relay)
Contact load relay	30 V DC/1 A
Application temperature	-20 °C ... 72 °C
Storage temperature	-25 °C ... 75 °C
Connection terminal	\varnothing 0.6 mm to 2 mm ²
Material	ABS
Air humidity	< 95 % (non-condensing)
Color	white, similar to RAL 9010
Weight	approx. 80 g
Dimensions	\varnothing : 117 mm H: 24 mm (incl. detector 62 mm)



Cable entry on the side or through the bottom plate. Connection of remote indicators not allowed!
Wago clamps for looping in wires, e.g. type 243-204 (\varnothing 0.5 mm - 1.0 mm) or 273-104 (0.75 mm²- 2.5 mm²) can be mounted on the detector base.
Not suitable for application with IQ8Quad with integrated alarm device Part No. 802383, 802384, 802385 and 802386 as well as 802385.SVxx and 802386.SVxx!